

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
25 November 2004 (25.11.2004)

PCT

(10) International Publication Number
WO 2004/102763 A1

(51) International Patent Classification⁷: **H02H 3/253**

(21) International Application Number:
PCT/FI2004/000289

(22) International Filing Date: 13 May 2004 (13.05.2004)

(25) Filing Language: Finnish

(26) Publication Language: English

(30) Priority Data:
20030732 15 May 2003 (15.05.2003) FI

(71) Applicant (for all designated States except US): **ABB OY**
[FI/FI]; Strömbergintie 1, FI-00380 HELSINKI (FI).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **MIETTINEN, Erkki**
[FI/FI]; Kirkkokatu 1 B A 1, FI-00120 HELSINKI (FI).

(74) Agent: **SEPPO LAINE OY**; Itämerenkatu 3 B, FI-00180
HELSINKI (FI).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PHASE FAILURE DETECTOR AND A DEVICE COMPRISING THE SAME



(57) Abstract: This publication discloses a phase failure detector (1) for a multi-phase electricity supply network. The phase failure detector includes one detector circuit (3) for each phase (2), which has a first connection point (4) for connecting to the phase (2) being monitored and a second connection point (5), which is connected to a common connection point (9) of the detectors circuits. The detector circuits (3) in turn include capacitive voltage divider elements (6), which are located between the first (4) and the second (5) connection point and with the aid of which reduced voltage is divided and fed to a trigger and detector circuit (8), which is arranged to produce a detection pulse when the reduced voltage reaches a trigger value.